

6" HALF-ROUND COPPER WORK SHEET

Name		Date	PO#	Residential delivery yes/no
Shipping address		City	State	Zip
Phone	Fax	E-mail		Alt. phone
Qty.	Revised 8.18			Price
	<u>Gutter 6" half round copper gutter</u> <i>Indicate gutter quantities below;</i> ____ pcs @ 6ft. ____ pcs @ 10ft. ____ pcs @ 15ft. ____ pcs @ 20ft. ____ pcs @ 26ft.			20 oz.
				16 oz.
	<u>Gutter shipping box</u> (necessary for shipping) Classic Gutter Systems, LLC will calculate.			\$ 2.75 box foot
	Hanging devices-recommended spacing every 32" on center			
	<u>Cast fascia bracket</u> (solid brass) style _____ <u>circle</u> screw or tab (for front attachment)			\$ each
	<u>Cast fascia bracket wedge</u> (solid brass) for angled fascia <u>circle</u> 7.5° 15° 22.5° 30° 37.5° 45°			\$ each
	<u>Stamped fascia bracket - copper</u> (requires a 4 to 4 1/2" fascia)			\$ each
	<u>Cast wedge for stamped fascia bracket - (solid brass)</u> for angled fascia 7.5° 15° 22.5° 30° 37.5° 45°			\$ each
	<u>Hanger unit</u> includes .060 stainless steel bracket & 11" s. steel 5/16" rod and nuts 13" rod add .50			\$ each
	<u>Rod bender</u> recommended to bend stainless steel rods, deposit refunded upon a 2 month return			\$ 250.00 deposit
	<u>End cap 16 oz.</u> _____ left _____ right			\$ each
	<u>Spherical end cap 16 oz.</u> (reversible -fits both ends)			\$ each
	<u>Miter 3" wide strip</u> (____ outside 90°) (____ inside 90°) (____ outside 45°) (____ inside 45°)			\$ each
	<u>Outlet 16 oz. 4" round copper outlet</u> (inside/outside mount)			\$ each
	<u>Funnel outlet - outside mount</u> to be used with 4" downspout			\$ each
4" elbows & downspout 72° elbows 2 = 9" offset 40° elbows 2 = 3" - 9" offset				
	<u>Elbow (folds in bend)</u> 16 oz. <u>circle</u> CORRUGATED or SMOOTH _____ 40° _____ 72°			\$ each
	<u>Downspout 16oz.</u> <u>circle</u> CORRUGATED or SMOOTH round (10' sections)			\$ section
	<u>Welded seam elbow (completely smooth)</u> 18 oz. 4" round _____ 40° _____ 72° 72° elbows 2 = 9" offset 40° elbows 2 = 3" offset			\$ each
	<u>Welded seam downspout</u> 18 oz. 4" smooth round (9'10" sections)			\$ section
	<u>Downspout strap</u> 16 oz. 15" x 2 1/4" copper			\$ each
	<u>Cast downspout stirrup & spring</u> (solid brass) provides a 1" standoff for 4" round downspout			\$ each
	<u>Cast downspout bracket</u> <u>circle</u> flush mount or 3" projection style _____			\$ each
	<u>Stamped downspout bracket</u> 4" copper <u>circle</u> flush mount or projecting			\$ each
	<u>Steel bolts for projecting stamped brackets - circle</u> projection offset needed (2 1/2" - \$1.50) (4" - \$1.95) (6" - \$2.75)			\$ each
	<u>Gutter screen</u> 3' x 8" x 20 oz. copper screen (3' sections only)			\$ each
	<u>Strainer - 4" copper</u>			\$ each
	<u>Solder</u> 1# spool acid core 1/8" wire (60% lead 40% tin)			\$ each
	<u>Misc.</u>			\$ each
	<u>Misc.</u>			\$ each