

5" COPPER K-STYLE GUTTER WORK SHEET FORM

Name		Date	PO#	Residential delivery yes/no
Shipping address		City	State	Zip
Phone	Fax	E-mail		Alt. phone
Qty.	Hanging devices- recommended spacing every 32" on center	Revised 3-19	Price	Total
	5" K-style gutter - copper		20 oz. \$ ft \$	
	____ pcs @ 6 ft. ____ pcs @ 10ft. ____ pcs @ 15ft. ____ pcs @ 20ft. ____ pcs @ 26ft.		16 oz. \$ ft \$	
	Radius copper gutter - 5" k-style (90" sections)		\$ /sect \$	
	Gutter shipping box (necessary for shipping) Gutter box \$2.50 per foot / Crate for radius gutter \$65		\$ \$	
	5" k-style hidden gutter bracket - .060 stainless steel		\$ each \$	
	End cap 5" k-style - copper ____ left ____ right		\$ each \$	
	Miter -strip type 3" wide copper (____ outside 90°) (____ inside 90°) (____ outside 45°) (____ inside 45°)		\$ each \$	
EXCLUSIVE 5" DECORATIVE K-STYLE FASCIA BRACKET ACCESSORIES				
	Open Curl decorative fascia bracket accessory - 5" cast brass k-style		\$ each \$	
	Queen Anne decorative fascia bracket accessory - 5" cast brass k-style		\$ each \$	
	Weathered Flat Plain decorative fascia bracket accessory - 5" cast brass k-style		\$ each \$	
3" round elbows & downspout				
72° elbows 2 = 8" offset 40° elbows 2 = 2" - 7" offset				
	Outlet 16 oz. 3" round copper (flat bottom interior outlet)		\$ each \$	
	Elbow (folds in bend) 3" x 16 oz. round <u>circle</u> CORRUGATED or SMOOTH ____ 40° ____ 72°		\$ each \$	
	Downspout 3" x 16 oz. round <u>circle</u> CORRUGATED or SMOOTH round (10' sections)		\$ section \$	
	Welded seam elbow (completely smooth) 18 oz. 3" round ____ 40° ____ 72° 72° elbows 2 = 8" offset 40° elbows 2 = 2" offset		\$ each \$	
	Welded seam downspout 18 oz. 3" smooth round (9' 10" sections)		\$ section \$	
	Downspout strap 16 oz. 15" x 2 1/4" copper		\$ each \$	
	Cast downspout stirrup & spring (solid brass) provides a 1" standoff for 3" round downspout		\$ each \$	
	Stamped downspout bracket 3" copper <u>circle</u> flush mount or projecting		\$ each \$	
	Stainless Steel bolts for projecting stamped brackets - <u>circle</u> projection offset needed (2 1/2" - \$1.50) (4" - \$1.95) (6" - \$2.75)		\$ each \$	
	Cast downspout bracket <u>circle</u> flush mount or 2 1/4" projection style _____		\$ each \$	
3" x 4" rectangular downspout & accessories				
	Outlet 16 oz. 3" x 4" rectangular wide flange (mounted inside the gutter)		\$ each \$	
	Elbows - 16 oz. 3" x 4" rectangular ____ A ____ B		\$ each \$	
	Downspout 16 oz 3" x 4" rectangular downspout (10' sections)		\$ section \$	
	Gutter screen 3' x 8" x 20 oz. copper screen (3' sections only)		\$ each \$	
	Strainer - 3" copper		\$ each \$	
	Foam Filter - 5" k-style Leaf Defier gutter foam - 4 ft sections		\$ section \$	
	Solder 1# spool acid core 1/8" wire (60% lead 40% tin)		\$ each \$	